

Phone: 800-253-6300 Fax: 201-337-6540 mulhernbelting.com sales@mulhernbelting.com

Part Number 1-1250

U2BL POLI-GLIDE 8M/2U/BU



Color: Blue

Nominal OAG: 0.070" +/- .010

Plies: 2

Fabric: Polyester

Minimum Pulley Diameter: .6

Top Surface: Smooth **Bottom Surface:** Bare **Compound:** Urethane

Work Tension: 126 lbs./PIW Elongation: Less than 1% Weight P.I.W. / Ft.: .026

Working Temperature: -4F to 212F Joining Method: Finger Splice; Lacing

Mulhern Belting's **1-1250** is FDA compliant, has a non-adhesive cover, is abrasion resistant and has good edge wear. The unique blue color helps visibility on food inspection lines.

U2BL Poli-Glide 8M/2U/BU is a good food application belt. It is used as an accumulation belt, a diverting belt, a dough belt and a general conveying belt in food applications.







- Service
- In-House Fabrication
- Multiple Stocking Locations
- On-Time Delivery
- Quality





Lacing

The complete Flexco line of products: Standard Lacing; Recessed Lacing; Hidden Lacing; Cover Flap Lacing; Plastic Rivet Lacing; Plastic Spiral



Endless

Complete Thermoplastic and Rubber Vulcanization: Lap Splices; Finger Splices; Double Finger Splices; Skived Splices; Stitched Reinforcement; **Prepared Ends**



Thermoplastic Profiles

Tee Cleats; Beefy Cleats; Scoop Cleats; Thin Line Cleats; Fabric **Reinforced Cleats: Curved Cleat** Patterns; Chevron Cleat Patterns; V-Guides; Flanges; Lugs; Sidewall with and without a base



Hot-Molded Rubber Profiles

Sidewall; Tee Cleats; SI Cleats; Scoop Cleats; Lugs; V-Guides; Flanges; Chevron Patterns; Bucket Patterns; Versa Patterns



Specialty Fabrications

Longitudinal Splicing; Covered Timing Belts and V-Belts; APC Belts; Capped Edges; Pulley Lagging; Loop Belts; Teflon Fiberglass Mesh Belts; Grooved and Beveled Belts; Splice Kits



Hole Punching

Punching for Bucket Elevators or Perforations

Phone: 1-800-253-6300 Fax: 1-201-337-6540

sales@mulhernbelting.com